

West of Shetland Case Study

Presented by: Mark Siegmund

Prepared by Multiple SUT Houston Volunteers



Subsea Operations Case Study




WoS Overview

- Situated in Atlantic Ocean, 180km West of Shetland
- UKCS block 204
- Jointly owned by BP, Shell, Amerada Hess and others
- Over 650 million barrels reserves
- Fields discovered in early 1990s
- Foinaven started production November 1997, Schiehallion June 1998.



WoS Overview - Location






WOS Overview - Challenges

- Water depth 350 to 500 metres
 - Formidable technical challenge
 - Too deep for divers
 - Totally reliant on unmanned intervention
- Remote from infrastructure of existing UKCS facilities
- Harsh environmental conditions and complex subsea currents
- Complex seabed architecture



WoS Overview - Environment


Met ocean conditions & currents



West of Shetland (Foinaven) Vs. East of Shetland (Magnus)



WoS Overview - Community



Environmental Sensitivities

- SEABIRDS
 - internationally important colonies
- FISHERIES
 - offshore and inshore
- CETACEANS
- COLDWATER CORALS
- ISLAND COMMUNITIES
 - Shetland & Orkney



Development Options

- TLP /Semi plus pipeline export too expensive - pipeline needed approx 500kbpd to be economic
- Semi (MODU) plus FSU
- FPSO Conversion
- New build steel FPSO




Development Selection

- The final selection driven by pace.
- The original Invitation to bid was based on a throughput of 55kbpd and a desire for early oil. FPSO conversion promised 18 months or less delivery. In the tender evaluation this was increased to 75kbpd (and later at sanction to 85Kbpd). Given the pace demanded new build semi's were out and only the Steel Semi/FSU and the FPSO conversion were serious contenders
- FPSO conversion selected



Project Schedule







FPSO

- Uses proven technology
- Flexible can accommodate changes in design basis
- Requires relatively short project schedule
- CAPEX requirement relatively low
- Oil storage inherent in design
- Can be relocated minimize abandonment costs



FPSO

FOINAVEN

- Conversion of submarine support vessel Anadyr (Astano, Spain)
- Consortium built. Owned and operated by GNO - leased by BP
- Max throughput 120mbd
- Storage capacity 300,000 bbls
- Full thruster system
- Length 250m

SCHIEHALLION

- New Build (Harland and Wolff, Belfast)
- Owned and operated by BP
- Max throughput 220mbd
- Storage capacity 950,000 bbls
- Limited thruster power
- Length 250m




Foinaven





Foinaven






Schiehallion






Subsea Architecture






Subsea Layout





Subsea Facilities and Equipment






DMaC Concept

<u>Diverless Maintained Cluster</u>

- Diverless pull-in and connection of flexible pipe
- Fly to place installation of umbilical jumpers
- Choke and control module changeout
- Manifold removable valve module (RVM) changeout



DMaC Concept






DMaC Pull-in-Tool & ROV










DMaC Tie-in






DMaC "Fly-to-Place" Umbilical Jumper Connection








Tree







Development Features

- 74 Well Development
- 11 Drill Centres
- 12 Production manifolds
- 6 Water injection manifolds
- 3 Gas injection manifold
- 66 Flowline Termination Assemblies


- 155km Linepipe
- 40km Static umbilical
- 3km Dynamic Umbilicals
- 17km Dynamic risers
- 280 Fly to Place Connections



Schiehallion Subsea Equipment

Those'Other Bits'

(8 Production Manifolds, 6 Water Injection Manifolds, 1 Gas Injection Manifold, 36 FTA's)



Plus:


21 Production XT's, 21 Water Injection XT's, 1 Gas Disposal XT, 85 Km Linepipe, 4 Km of Flexible Jumpers, 14 Flexible Risers, 16.7 Km Control Umbilicals, 2 Dynamic Umbilicals, 5.9 Km of Control Jumpers, 25 Control Structures, 146 DMaC Connections & Pullheads, 126 FTP Connections, 14 Suction Anchors, 25 Km of Mooring Lines

Repeat all of the above for Foinaven



Foinaven Lessons Learned

Central Production Manifold With Lift Frame



Dimensions 24ft x 36ft x 36ft high




Manifold - Hubs

- Manifold and hubs made of super duplex steel.
- Cracks at hubs discovered during testing of installed manifolds.
- Manifold recovered and reworked to reduce strength of CP system and reduce build in stresses in pipe work.



Manifold - Hubs






Manifold - Stem Seals

- Deformation and leakage of valve stem seals discovered during testing
- Manifold installed with atmospheric pressure trapped inside
- Stem seals exposed to external seawater pressure
- Stem seals modified to eliminate problem during manifold re-work




Manifold - Stem Seals






Foinaven Development Schedule





Impact

- Project delivery
 37 vs. 15 months
- Subsea CAPEX
 640 vs. 320 \$mm
- FPSO CAPEX 510 vs. 320 \$mm
- BP share
 1405 vs. 823 \$mm






DCV's



Scanning electron micrograph showing the extensive loss of metal from surface of balls used in pilot stage of Directional Control Valve



Micrograph showing intergranular corrosion attack



Tree Sensors








Connectors / Penetrators






Choke Hydraulic line failure






Hydraulic Coupler Circlips





Riser Damage





Conclusion

- Foinaven and Schiehallion are amongst the most successful subsea producing fields in the BP portfolio with over 120 wells drilled
- The projects have been a significant source of learning given the early set backs
- Unique set of failures was a catalyst to launch the BP subsea reliability initiative – BP ETP's & API 17N
- WOS remains a source for continued Innovation and Lateral thinking – eg. Drill Through Trees

.....Questions?