

Offshore Pipeline Installation

Presented by:
Naveen Ravirala

Author:
Craig Lamison

Pipeline Installation

Definitions

- Primarily covers steel pipe
- 3" nominal diameter and up
- Other alternatives:
 - Flexible pipe
 - Coiled tubing
- Welded connections used for pipelines
- Mechanical connections viewed as:
 - Less reliable
 - More expensive

Definition - Installation

- Fabricating line from joints above water
- Placing line undamaged on the seabed
- Associated activities such as
 - Initiations/Terminations
 - Abandonment/Recovery
 - Tie-ins
 - Risers
 - Burial
 - Shore Approach


What Can Go Wrong – Pipe Buckle



Pipeline/Flowline Installation

- Offshore Fabrication
 - S-Lay (conventional pipelay)
 - J-Lay
- Onshore Fabrication
 - Reel-Lay
 - Tow

S-Lay (Conventional Pipelay)



Castoro Sei

S-Lay History

- First “offshore” pipeline
- Galveston Bay
- Laid by Brown & Root
- Technology adapted from marsh lay
- Linked “Spud” barges



S-Lay (Conventional Pipelay)



Solitaire


S-Lay (Conventional Pipelay)



S-Lay

Monohull (Hercules, DB-16, Solitaire etc.)

- Semi-submersible (Castoro Sei, Semac)
- Lay rates typically on order of 2.0 miles per day
- Commonly used for shallow water
- Some dynamically positioned deepwater vessels
- Good for long distance & large diameter pipelines




S-Lay

- Pipe brought aboard in 40-80 ft. “joints”
- Joints welded end-to-end on “firing line”
- Firing lines consist of:
 - welding stations (5-7)
 - NDE (Non-Destructive Examination or Testing - NDT) station (1)
 - field joint coating/accessory stations (1-3)

S-Lay

Schematic




S-Lay Welding



S-Lay Limitations


- S-lay uses a “stinger” on the stern of the barge to support the pipe “overbend”.



- Stingers are up to 300 feet long & curved for deepwater
- Radius of curvature selected to avoid pipe overstress
- Sharp radii for small dia. lines, large radii for large lines
- S-Lay generates very high top tensions
- Pipe may undergo plastic strain in the overbend


S-Lay Limitations

- Fatigue damage may occur in the pipe near the stinger tip if pipelay halted with pipe suspended.




- **Sacrificial anodes collared/tapered to pass over stinger rollers**
- **Special procedures to handle PLEMs and PLETs (Pipeline End Manifolds or Terminations) over stinger**
- **Alternatively attach PLEMs and PLETs by:**
 - **lowering pipe to seabed**
 - **recovering pipeline to side of vessel**
 - **welding on the PLEM/PLET & lowering**

Vessels don't turn on a dime



J-Lay




Modular J-Lay



J-Lay Methodology

- Quad jointing (4) or hex jointing (6)
 - May be done onshore or offshore
- As with S-Lay, remaining welding on vessel
- Multi-joints are upended
- Welding in vertical or near-vertical configuration.
- Pipe may be supported:
 - On forged steel J-lay collars welded to pipe
 - By tensioners

J-Lay Schematic



J-Lay Advantages


- Easy to deploy pipe vertically reducing top tension
- Good for very deep water (6,000 feet plus)
- Configuration good for SCR (Steel Catenary Riser) installation
- Stinger is eliminated.
- No plastic straining of pipe.
- PLEMs and PLETs can be lowered through moonpool (subject to size).


J-Lay Disadvantages

- Slowest of all current pipelay methods
 - order of 1 mile per day.
- Still requires some welding offshore.
- Cycle times are long
 - all operations at one work station.
- If need J-lay collar, forgings add to cost
- Limited in shallow water based on diameter



Reel Lay

 The image cannot be displayed. Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

 The image cannot be displayed. Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

Technip Deep Blue



Cal Dive Kestrel






Global Chickasaw



Subsea 7 Scandi Navica



Reel-Lay History - Operation PLUTO



Pipelines under the ocean

- D-Day June 1944
 - 4-inch pipelines laid from England to France
 - Fuel for Allied invasion forces.
 - Lead pipe, wrapped in steel reinforcing cables
 - Coating -- coal tar enamel
 - Wound onto large floating reels or “conundrums”
 - Reel towed across Channel laying pipe
- 1945
 - Hopper dredge HMS Persephone converted to vertical reel
 - Laid rigid steel pipe as first reel ship.

Horizontal Reel Barges

Santa Fe Reel Barge

- RB-2 “Chickasaw”, 1970
 - Purpose-built barge
 - In service with Global Industries
 - Upgraded w/dynamic positioning




Technip Deep Blue



Technip Deep Blue

- Dual reels hold 5600 metric tons
 - 4-inch to 18-inch diameter pipe.
- Additional 5600 tonnes of storage
 - on deck for J-lay pipe
 - under-deck baskets/on-deck carousels for umbilicals
- Reel-lay up to 550 tonnes top tension
- J-lay up to 770 tonnes top tension.

Subsea 7 Seven Scandi Navica



Subsea 7 Seven Navica

- 2500 ton reel capacity
- 2" – 16" Pipe
- Single load approximately:
 - 43 miles of 6"
 - or 7.5 miles of 16"
- 250 Short ton tensioning capacity

Spoolbase Fabrication



Mobile Spoolbase, Alabama



Pipe Spooling at Mobile



Reeling 18-Inch Pipe



Advantages of Reeled Pipe

- Fabrication is performed onshore
- Controlled environment, off the critical path
- Weld repairs are performed on onshore
- Lay rates of up to 10 miles per day
- No stinger w/ J-Lay configuration for vertical reel
- Stinger required for horizontal reel

Disadvantages of Reeled Pipe

- Requires stringent pipe quality control
 - Match dimensional & mechanical properties.
- Requires testing of coatings and field joints
 - Bending strains of up to 2% on reel
 - High crushing loads on reel.
- Pipe undergoes plastic straining
 - Marginally affects fatigue performance.
- Rule of thumb, requires D/t ratio < 20
 - Results in thicker pipe in shallow waters
- Concrete weight coatings not feasible
- Integral buckle arrestors cannot be used.

Muddy Waters – Combination Vessels

- Acergy Falcon




– S-lay firing line

– reel lay vertical stinger & straightener

Installation Methods vs. OD & WD

Traditional Limitations



Pipe fabrication limitations can also govern

Installation State of the Art is Advancing

- Largest diameter pipelines -- 56" (Shallow)
- Large deepwater pipelines
 - Blue Stream Pipeline (J-Lay Saipem 7000)
24", 6900' WD
 - BP/Shell Okeanos Gas, NaKika, 24", 7,300' WD
 - BP Proteus Oil to Thunder Horse 28", 5,350' WD
 - Vessels for BP jobs
 - Heerema's J-lay Balder >3,700'
 - Allseas' S-Lay Solitaire < 3,700'
 - Independence Hub, 24" PL, 20" SCR Solitaire
~8000' WD
 - SCR Hang-off by Balder



Installation State of the Art -- Continued

- Large deepwater pipelines (Cont'd)

- Independence Hub, 24" PL, 20" SCR

- Solitaire ~8000' WD

- SCR Hang-off by Balder

- Perdido

- 18" PL & SCR

- Solitaire 8,250' WD



Universal Installation Activities

- Pipe Haul
- Sorting
- Welding
- Inspection
- Field Joint Coating

Pipe Haul



Ready Racks - Pipe Sorting



Pre-Heat



Internal Line-Up Clamp



Root and Hot Pass



Fill and Cap



Radiographic Examination



Radiographic Interpretation

- Note AUT Alternative Allows Digital Interpretation



Field Joint Blasting



Field Joint Coating Application




Towed Pipeline Installation

- Two common methods
 - Controlled Depth Tow Method (CDTM)
 - Bottom Tow
- CDTM, North Sea & Australia
- Bottom Tow, Gulf of Mexico

CDTM Fabrication Site



CDTM Technique



CDTM Launch



Bottom Tow Launch

- Enserch GB 387 Tie-Back
- 28" Casing
- Six 3" Flowlines & Umbilical



Bottom Tow Fabrication Site



Tow Advantages

- Onshore fabrication & quality control
- Installs multiple bundled lines at once
- Can be readily insulated
- Rapid offshore installation
- Inexpensive offshore spread
- Low stress even in deepwater

Tow Disadvantages


- Limited by length of fabrication site
 - CDTM ~7 km
 - Bottom tow ~ 7 miles
- Longer lines require offshore connection
- Bottom tow requires extensive survey
- Few fabrication sites
- Requires delicate weight balance

Associated Activities

- Pipeline Burial
- Pipeline Terminations
 - PLETs, FLETs, & PLEMs
 - Jumpers
 - SCRs
 - Shore Approaches

Pipeline Burial






Pipeline Jumper Installation




Steel Catenary Riser (SCR) Installation



J-Lay or Reel SCR Installation Method



J-Lay or Reel SCR Installation Method




Shore Approach



- Petronas Carigali, Malaysia
- Three 30" Pipelines

Questions?



Nebula Laying
Twin 56" Water
Lines, Sydney
Harbor, 2009